A. Questions about the ideal heating load:

1. When using a schedule in TRNbuild (see figure 1) I notice that:

- Somehow the heating only switches on at exactly the time of the switch (in my case 7 h and 17 a. h), while I assumed the schedule to mean that at the new time the new temperature must be obtained. The heating switches OFF at exactly the changing time, so it then takes the new setpoint temperature. (see figure 2)
- More strange I find that it takes two hours for the temperature to reach the setpoint b. temperature..

In case I take 0,5 hr timestep, it takes an hour to reach the setpoint temperature. So in general it takes two timesteps for the ideal heating to reach the required setpoint ...

Is this normal or what am I doing wrong?

Fig 1. my schedule within TRNbuild

In TRNbuild I included a heating schedule as follows:

0	-	7h	16 oC
7	-	17h	19 oC
17	-	23h	21 oC
~~		0.41	41 0

Schedule Type Managerxxx	23	-	240	í	10 00	
Control <t< th=""><th>chedule Type</th><th>Managerxo</th><th>OK</th><th></th><th></th><th></th></t<>	chedule Type	Managerxo	OK			
@ daily C weekly Daily From Until Value 0030 0730 1600 0740 1700 1900			A schedu	lle type:	SCH_LIV_RM	
Daily From [Unit] [Value] 0050 0750 1500 0750 1750 1900 17400 23400 2100				6 daily	C weekly	
From [Until [Value 00:00 07:00 16:00 07:30 17:300 19:00 17:400 23:400 21:00		Daily -				
00:00 07:00 16:00 07:00 17:00 19:00 17:00 23:00 23:00	From	Until	Value	-		
07:00 17:00 19:00 17:00 23:00 21:00	00:00	07:00	16.00			
17:00 23:00 21:00	07:00	17:00	19.00			
23.00 24.00 16.00	17:00 23:00	23:00 24:00	21.00 16.00			
Add Delete	Add	De	lete	1		
from until value	fro	m until	value			
h: 0 7	h: 0	7	16			
min: 0 0	min:	0	10			
	OK					

Figure 2: comparing the resulting indoor air temperature (pink) with the setpoint as produced



with an equation solver.

In order to compare the resulting indoor air temperature with the setpoint schedule I also plotted a schedule produced in an equation solver, as follows:

 $LT(hr_day, 7)*16+(GT(hr_day, 7)+eql(hr_day, 7))*LT(hr_day, 17)*19+(GT(hr_day, 17)+eql(hr_day, 17))*(LT(hr_day, 23)+eql(hr_day, 17)+eql(hr_day, 17))*(LT(hr_day, 17)+eql(hr_day, 17)+eql(hr_d$ y,23))*21+GT(hr_day,23)*16

Where:

 $Hr_day = hour of the day = mod(time,24)$

2. Implementing a setpoint as an input from the equation solver.

In this case I used the above described schedule from the equation solver as an input for the heating in TRNbyuild.

1111	voyunu.						
Heat	ting - room te	mperature contr	ol [°C	1			
•	Constant Valu	e 1	<	- new Y	+ 0		
C	Schedule						
	For night set back, use on/off schedule addition factor: nighttime temperature multiplication factor: daytime temperature increase						
_							
	ок	Cancel					

(I cannot use an on /off schedule as suggested in red, since the required schedule is more complicated.)





Question:

In this case the heating switches on at the time the setpoint goes up. Bus still it takes two timesteps before the setpoint temperature is reached. Does anyone know why?

B. Question about the simulation:

Does anyone know why the temperature seems to be fluctuating a little (in other words: it is not a smooth line) as soon as the heating turns off?

Also when using a smaller timestep the line is not smooth, but the temperatures stay constant during a hour, so the line looks like a staircase..

(note: the non-smooth line occurs when the heating is OFF)



Is this normal and if so, why is this kind of fluctuation / pattern the result? Or am I doing something wrong?

Thank you very much again.

Sabine